

Dale BESS

NBN-P30, NBN-P50, NBN-P100



FEATURES



REMOTE
MONITORING



ENGINEER
INSTALLATION



DC COUPLING
WITH SOLAR



1 + 1
BATTERY



HIGHLY
EFFICIENT



24 HOUR
MONITORING

HIGHLIGHTS

- Safe and reliable
- CE certified.
- Simple and user-friendly
- Economical and efficient
- Peak load shifting capability
- 5 Tier safety design
- Integrated BMS/EMS, suitable for various applications
- Distributed energy integration
- Long lifecycle/strong battery strength
- Cloud-terminal smart battery management algorithm.
- Efficient and energy-saving HVAC design

Integrated Outdoor Battery Energy Storage Cabinet

MODEL	NBN-P30	NBN-P50	NBN-P100
Battery Parameters			
Cell Type	LiFePO4 - 280Ah		
Battery Module Type	1P20S		
System Capacity Range	125kWh~215kWh	125kWh~215kWh	215kWh
AC Side On-grid Parameters			
Grid Type	3P4W		
Charging/Discharging Power	30kW	50kW	100kW
Rated Grid Voltage	AC400 (±15%)V		
Frequency Range	50(±5)Hz		
Rated AC Output Current	43A	72A	144A
Power Factor	0.8 (Leading)~ 0.8 (Lagging)		
Harmonics	≤3% (@rated power)		
AC Side Off-grid Parameters			
Load Type	3P4W		
Rated Output Power	30kW	50kW	100kW
Rated Output Voltage	AC 400V±1%		
Rated Output Frequency	50Hz		
Frequency Accuracy	0.2Hz		
Rated Current	43A	72A	144A
General Parameters			
Dimension (W*H*D)	1686mm*2093mm*1354mm		
Max. Weight	2500kg		
Ingress Protection	IP55(Battery Cabinet) IP54 (Electrical Cabinet)		
Cooling Method	HVAC (Battery compartment) & Forced air cooling (Electrical compartment)		
Fire Fighting System	Combustible gas detection + Novec1230 + water fire suppression		
Anti-Corrosion Grade	C3		
Relative Humidity	0-95% (non-condensing)		
Operating Temperature	-20°C - 50°C		
Operating Altitude	<2000m		
Noise Emission	≤75dB		
Communication Interface & Protocol	Rs485, Ethernet; Modbus RTU, Modbus TCP/IP HMI		
Display	HMI		
Warranty	5 years, (can be extended to 10 years)		
Certifications	CE(IEC61000,IEC62477), IEC62619,IEC62109,UN3480,CEI021,CEI016, VDE2510 Converter: G99, VDE4105, EN50549, AS/NZS 4777, CE(IEC61000, IEC62477) ,IEC62109, NC RfG, NRS097,VDE4110(on going) Cell: IEC62619, UL1973, UL1642, UL9540A PACK: UN38.3		



DALE POWER SOLUTIONS

Looking for something more bespoke?

We can provide you with design consultancy, manufacture and ongoing maintenance for our products.

What we do

- Design, manufacture, installation, commissioning and servicing
- Experts in customised BESS solutions
- In-house mechanical and electrical design capability
- Solutions for any environment, application and location
- In-house project management team to manage the development and delivery of your product for exactly when you need it.

Get in touch with our team today to discuss your requirements.

hello@dalepowersolutions.com
0330 999 3000
dalepowersolutions.com